

PRODUCT DESCRIPTION

- Designed to reach an IP67 waterproof rating
- Possible to obtain a line of light
- A wide range of available accessories
- Possible to bend the profile

FINISH:	
Silver anodized	
*Custom colors available upon	request
	Fill empty fields
Product nr.	
Fixture type	
Company	
Job name	
Date	



TECHNICAL SPECIFICATION

Application

- construction of lighting fixtures for main or decorative lighting

Assembly

- suitable for mounting on flat surfaces, suspending from <u>DP</u> fasteners, for attaching to mounting systems and for fixing with mounting springs, to ARMSTRONG ceilings with the <u>AM-24</u> mounting bracket
- compatible with a group of profiles dedicated to drywall panels. It is designed for mounting in the $\underline{\mathsf{TEKNIK-ZM}}$ and $\underline{\mathsf{TEKUS}}$ profiles using $\underline{\mathsf{TEKNIK}}$ latches

Number of latches:

Profile length	1	2	3
	m	m	m
Number of TEKNIK latches	8	18	28

Additional information

- possibility of making a linear fixture with IP67 protection, which means the fixture is dustproof and waterproof
- achieving IP67 is possible with the following covers: LIGER-22, MUN-22 and HS-22
- can be mounted in a groove made using a mounting extrusion
- a line of light obtainable with the LIGER-22 cover and a LED strip with a minimum of 120 LEDs/meter
- GIZA-LL is designed for two or one 10 mm wide LED strip

Profile bending

Minimum internal radius	Minimum external radius
-------------------------	-------------------------




250 mm	350 mm


- minimum radius bending radius which when exceeded causes destruction (deformation, bending or lack of compatibility with other accessories, e.g. covers, end caps, etc.) of the profile
- internal radius refers to the profile bent so that the cover is facing the inside of the arch
- external radius refers to the profile bent so that the cover is facing the outside of the arch
- irregular curves are possible after consultation and individual quotation
- when bending anodized profiles, one should be aware of cracking of the anode coating (which may be more or less visible depending on the radius)

AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C0758ANODA_1	Silver anodized	1000 mm
C0758ANODA_2	Silver anodized	2000 mm
C0758ANODA_3	Silver anodized	3000 mm


TECHNICAL DRAWING






GIZA-LL profile and AM-24 mounting bracket profil GIZA-LL z mocownikiem AM-24







GIZA-LL profile and GIP mounting bracket profil GIZA-LL z mocownikiem GIP



GIZA-LL profile and REGIP-UV mounting bracket profil GIZA-LL z mocownikiem REGIP-UV




GIZA-LL profile and REGIP-UV mounting bracket profil GIZA-LL z mocownikiem REGIP-UV



GIZA-LL profile and REGIP-UV mounting bracket profil GIZA-LL z mocownikiem REGIP-UV



RELATED PROFILES







TEKUS Profile Ref: B6638V1



TEKUS-ZM Profile Ref: C1293



TEKNIK-ZM-TK Profile Ref: C1554



RELATED PRODUCTS

COVERS



G-K frosted Cover Ref: 17007



transparent Cover Ref: 17006 Ref: 00415




G-L clear Cover



G-L frosted Cover Ref: 00413



G-L semi-transparent Cover Ref: 17008



HS-22 clear Cover Ref: 17022




HS-22 frosted Cover Ref: 17011



LIGER-22 black Cover Ref: 17044



LIGER-22 frosted



MUN-22 semitransparent Cover Ref: 17042



END CAPS



GIZA-LL grey End cap Ref: 24281

ACCESSORIES





BZP Head Ref: 42213



BZP-ZO Head Ref: 42214



BZP-ZZ Head Ref: 42215



DP Fastener Ref: 00644



DP-ZO Fastener Ref: 00649



DP-ZZ Fastener Ref: 00651



FI-10-ZM-P Fastener Ref: 42244



FI-10-ZM-W Fastener Ref: 42242




GIP Mounting bracket Ref: 24332



GIP-UV Mounting bracket Ref: 24310



GIP-UV black Mounting bracket Ref: 24328



GP Spring Ref: 00293



Gland 6,4x3 Ref: 42264



M11 Fastener set Ref: 42609



M12 Fastener set Ref: 42610



M13 Fastener set Ref: 42611



MP-22 Masking cover black Ref: 17167L9005



MP-22 metallized Masking cover Ref: 17167



MP-22 white Masking cover Ref: 17167L9010



PUSZ-LIN-ZM Fastener Ref: 42256



PUSZ-LIN-ZM Fastener Ref: 42275



PUSZ-LIN-ZM black Fastener Ref: 42275L9005



PUSZ-PRET-ZM Fastener Ref: 42250



PUSZ-PRET-ZM Fastener Ref: 42276





PUSZ-PRET-ZM black Fastener Ref: 42276L9005



RD-1 Fastener set black Ref: 42650



RD-1 Fastener set silver Ref: 42649



REGIP-UV Mounting bracket Ref: 24271



RG-1 Fastener set black Ref: 42648



RG-1 Fastener set silver Ref: 42647



Soporte de montaje AM-24 Ref: 24235



TEKNIK Latch Ref: 24003



UCHO-ZM Hanger Ref: 42512



UCHO-ZM black Hanger Ref: 42525



W1 Fastener set Ref: 42602



W2 Fastener set Ref: 42603



W6 Fastener set Ref: 42604



W7 Fastener set Ref: 42605



ZM Block Ref: 42520



ZM-120 Connector Ref: 42728



ZM-120-G Connector Ref: 42308



ZM-135 Connector Ref: 42720




ZM-135-G Connector Ref: 42310




ZM-150 Fastener Ref: 42118




ZM-180 Connector Ref: 42717



ZM-45-G Connector Ref: 42338



ZM-500 Fastener Ref: 42119



ZM-60-G Connector Ref: 42304





ZM-90 Connector Ref: 42716



ZM-90-G Connector Ref: 42306



ZM-PION-120 Connector Ref: 42320



ZM-PION-135 Connector Ref: 42719



ZM-PION-45 Connector Ref: 42314



ZM-PION-90 Connector Ref: 42718



ZM-T45-G Connector Ref: 42324



ZM-T60-G Connector Ref: 42326



ZM-T90-G Connector Ref: 42328



ZM-X45-G Connector Ref: 42330



ZM-X60-G Connector Ref: 42332



ZM-X90-G Connector Ref: 42334



ZM-Y120-G Connector Ref: 42336

MARKETING MATERIALS



Display P230-90113M Ref: 90113M



Display P230-90156M Ref: 90156M



Foam 70263 Ref: 70263



Foam 70266 Ref: 70266