

PRODUCT DESCRIPTION

- Installation of lighting and stretch films in suspension
- High lumen output
- Mounting to 12 mm | 0.47" drywall
- Non visible aluminum elements
- Line of light flush with the surface

FINISH:

Non anodized (raw)



*Custom colors available upon request




Product nr.

Fixture type

Company

Job name

Date



TECHNICAL SPECIFICATION

Application

- lighting recessed in surfaces made of stretch film and in drywall

Mounting

- suspended or in drywall, using a dedicated mounting track, dedicated accessories and screws
- can be easily connected into runs
- the cover is cut to the length of the profile

Additional information


- the profile has grooves for the attachment of the hooks from the stretch film

AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
C3632NA_1	Non anodized (raw)	1000 mm
C3632NA_2	Non anodized (raw)	2000 mm
C3632NA_3	Non anodized (raw)	3000 mm



TECHNICAL DRAWING





RELATED PROFILES







FOLED-50-SUF Profile Ref: C3631



RELATED PRODUCTS

COVERS

FROSTED COVERS



FOLED-50 frosted Cover Ref: 17171

END CAPS

REGULAR END CAPS



FOLED-50-W End cap Ref: 24294

STEEL



FOLED-50 End cap Ref: 42676

ACCESSORIES

FASTENERS & MOUNTING ACCESSORIES



Spring hanger Ref: 79106



COMPONENTS FOR CONNECTING PROFILES



ZM-NA-90 Connector Ref: 42723



ZM-NA-120 Connector Ref: 42729



ZM-NA-135 Connector Ref: 42725



ZM-NA-PION-135 Connector Ref: 42727



ZM-NA-PION-90 Connector Ref: 42726



ZM-T45-G Connector Ref: 42324



ZM-T60-G Connector Ref: 42326



ZM-T90-G Connector Ref: 42328



ZM-X60-G Connector Ref: 42332



ZM-X90-G Connector Ref: 42334



ZM-Y120-G Connector Ref: 42336



ZM-NA-45 Connector Ref: 42339



ZM-NA-PION-120 Connector Ref: 42321



ZM-NA-PION-60 Connector Ref: 42317



ZM-NA-PION-45 Connector Ref: 42315



ZM-NA-180 Connector Ref: 42724

SEALING COMPONENTS



6 x 1.2 Gland Ref: 00802