

Profile GIZA-LL-ZMG

Ref. A04501

Ref. arch C4501

IP20

- Hidden light source
- No light slits at profile joints
- Minimalistic form
- Smooth profile walls
- Wide range of accessories

APPLICATION


- main and decorative lighting

MOUNTING


- to the surface or suspended, using dedicated accessories
- can be easily connected into runs and systems

ADDITIONAL INFORMATION

- thanks to the use of a dedicated blocker, visible light slits are avoided in the places where individual sections of the profile are joined
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ



TECHNICAL DRAWING



RELATED ACCESSORIES > RELATED COVERS

NAME		MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.
DILENSO	NEW	PC	56 %	clear	B17173 17173
MUN-22		PC	86 %	semi-transparent	B17042F 17042
LIGER-22		PC	62 %	frosted	B17032M 17032V1
			39 %	black	B17032C 17087
HS-22		PC	73 %	frosted	B17011M 17011
			94 %	clear	B17011T 17022

Profile GIZA-LL-ZMG

Ref. A04501

Ref. arch C4501

RELATED ACCESSORIES > RELATED END CAPS

NAME	MATERIAL	COLOR	REF.
GIZA-LL-ZMG	ABS	silver	C24467C02 24467
		black	C24467C07 24468

RELATED ACCESSORIES > OTHER RELATED ACCESSORIES



BLOKER

4-14

C40707C02

Ref. arch 40707