

PRODUCT DESCRIPTION


A ready set of elements for suspension and one-sided powering of a light-weight lighting fixture. The bottom fastener is equipped with an external connection for one pole of current. The 43 cm rod acts as a power conductor and the top fastener serves as a mount to drywall and a connection to the power supply

Fill empty fields


Product nr.
Fixture type
Company
Job name
Date



RELATED PROFILES




GIZA-LL profile
Ref: C0758




OPK-4 Profile
Ref: C0370




JAZ Profile
Ref: B8547




SILER Profile
Ref: B9325



MICRO-ALU Profile
Ref: B1888




TAMI Profile
Ref: B5390




PDS-4-ALU Profile
Ref: B1718




PDS-ZM Profile
Ref: B7696




REGULOR Profile
Ref: B468+43




TEST-74 Profile
Ref: W4507




TETRA-43 Profile
Ref: W4476




TETRA-78 Profile
Ref: W4508




GIZA Profile
Ref: B5556




LIPOD Profile
Ref: B5554




3035-O Profile
Ref: B8441




PDS-ZMG Profile
Ref: C1418



MICRO-HG Profile
Ref: C1419



PDS-ZM-PLUS
Profile
Ref: C2056



Profile LIPOD-50
Ref: C2609