

PRODUCT DESCRIPTION

- 2-year warranty on optical and mechanical properties
- Very good mechanical resistance
- Good fire resistance
- We recommend the HS cover for sealing fixtures

Fill empty fields

Product nr.

Fixture type

Company

Job name

Date



TECHNICAL SPECIFICATION

Material	PC
Available length	1000 mm, 1050 mm, 2000 mm, 3000 mm
UV resistance	yes

TECHNICAL DRAWING





RELATED PROFILES



OPK-4 Profile Ref: C0370



OLEK Profile Ref: B8505



PDS-4-K Profile Ref: B3776



45-ALU Profile Ref: B4023



DES Profile Ref: 18030



NISA-KRA Profile Ref: 18026



MICRO-H Profile Ref: C0599



MICRO-ALU Profile MICRO-K Profile Ref: B1888



Ref: B3775

PDS-H Profile

Ref: B9204

PDS-ZM Profile Ref: B7696 Ref: B6144



KUBIK-45 Profile Ref: B7697



NISA-PLA Profile Ref: 18028



STEP Profile Ref: 18042



45-16 Profile





PDS-O Profile Ref: B3777



Ref: 18040



NISA-KON Profile Ref: 18027



PULA Profile Ref: 18035



PDS-4-ALU Profile Ref: B1718



POLI Profile

Ref: B7176

NISA-NI Profile Ref: 18029





OBIT Profile Ref: W4826



45-MDF Profile Ref: 0973





PAC-MDF Profile Ref: 0972



PDS-MDF Profile Ref: 0971



PDS-4-PLUS Profile Ref: C1263



STOS-MDF Profile Ref: 0974



PDS-ZMG Profile Ref: C1418



MICRO-HG Profile Ref: C1419



PDS-ZM-PLUS Profile Ref: C2056



MICRO-NK Profile Ref: C1587

PDS-T Profile Ref: C2057