

## PRODUCT DESCRIPTION

- Fits all basic KLUŚ extrusions
- Cover dedicated to creating a line of light
- We recommend it to be used with bent extrusions
- Very good light diffusion
- The product is available in a 10 m roll

Fill empty fields



Product nr.

Fixture type

Company


Job name

Date


## TECHNICAL SPECIFICATION

Material	PC
Available length	1000 mm, 1050 mm, 2000 mm, 3000 mm, 10000 mm
UV resistance	increased


## TECHNICAL DRAWING



**RELATED PROFILES**



OPK-4 Profile  
Ref: C0370




MICRO-H Profile  
Ref: C0599




PDS-H Profile  
Ref: B9204




45-16 Profile  
Ref: B8504



OLEK Profile  
Ref: B8505




MICRO-ALU Profile  
Ref: B1888




MICRO-K Profile  
Ref: B3775



PDS-4-ALU Profile  
Ref: B1718




PDS-4-K Profile  
Ref: B3776




PDS-ZM Profile  
Ref: B7696



POR Profile  
Ref: B6144




PDS-O Profile  
Ref: B3777



45-ALU Profile  
Ref: B4023




GLAD-45 Profile  
Ref: B7009




KUBIK-45 Profile  
Ref: B7697



KOZMA Profile  
Ref: 18040




DES Profile  
Ref: 18030




POLI Profile  
Ref: B7176




NISA-PLA Profile  
Ref: 18028



NISA-KON Profile  
Ref: 18027




NISA-KRA Profile  
Ref: 18026




NISA-NI Profile  
Ref: 18029



STEP Profile  
Ref: 18042




PULA Profile  
Ref: 18035




OBIT Profile  
Ref: W4826



LIT-L Profile  
Ref: 18033




PDS-4-PLUS  
Profile  
Ref: C1263




PDS-ZMG Profile  
Ref: C1418




MICRO-HG Profile  
Ref: C1419




MOD-50 Profile  
Ref: 18047




PDS-NK Profile  
Ref: C1588




MICRO-NK Profile  
Ref: C1587



MOD-100 Profile  
Ref: 18049



PDS-T Profile  
Ref: C2057



PDS-ZM-PLUS  
Profile  
Ref: C2056